


RFC

Round Solid Profile

Material:	Volta FC, Clear
Hardness:	76 A
Temp. Range:	-40° C to +50° C
Certification:	FDA

Coefficient of friction:	
Steel:	0.65
Aluminum:	0.65
Rubber:	0.80



RFC

BELT TYPE	DIAMETER Ø mm	WEIGHT kg/m	MIN. PULLEY Ø mm	MAX. WORK LOAD kg	PULLFORCE (kg) AT PRETENSION		
					1 %	2 %	3 %
RFC - 5	5	0.024	25	1.6	0.30	0.60	0.90
RFC - 8	8	0.06	40	4	0.75	1.50	2.25

Notes:


1. Pull Force in tables relate to grooved steel, aluminum and Cast Iron pulleys.
Multiply given values by 0.7 for wet pulleys.
2. Dimensions have been converted from metric measurements.

RFC

Round Solid Profile

Material:	Volta FC, Clear
Hardness:	76 A
Temp. Range:	-40° F to +120° F
Certification:	FDA

Coefficient of friction:	
Steel:	0.65
Aluminum:	0.65
Rubber:	0.80



RFC

BELT TYPE	DIAMETER ∅ inch	WEIGHT lbs / ft	MIN. PULLEY ∅ inch	MAX. WORK LOAD lbs	PULLFORCE (lbs) AT PRETENSION		
					1 %	2 %	3 %
					RFC – 5	3/16	0.016
RFC – 8	5/16	0.040	19/16	6.6	1.65	2.3	4.95

Notes:

1. Pull Force in tables relate to grooved steel, aluminum and Cast Iron pulleys.
Multiply given values by 0.7 for wet pulleys.
2. Dimensions have been converted from metric measurements.