


VPO Trapezoidal Reinforced Cogged Profile

Material:	Volta PO, Black
Hardness:	95A / 46D
Temp. Range:	- 20°F to 140°F

Coefficient of friction :	
Steel:	0.35
Aluminum:	0.35
UHMW:	0.30



BELT TYPE	DIMENSION W x H inch x inch	WEIGHT lb / ft	MIN. PULLEY Ø inch	MAX. LOAD lb	PULLFORCE (lb) AT PRETENSION			DRILL BIT
					0.5 %	1%	1.5%	
VPO-10/Z (NK)	3/8 x 15/64	0.04	3	99	27	54	82	I
VPO-13/A	1/2 x 11/32	0.06	3	99	31	62	93	I
VPO-17/B	5/8 x 7/16	0.10	4	128	61	121	NR	II
VPO-22/C	7/8 x 35/64	0.17	5 3/16	258	79	159	238	III

Notes:

1. Pull Force in tables relate to grooved steel and aluminum grooved pulleys. Multiply given values by 0.7 for wet pulleys.
2. Dimensions have been converted from metric measurements
3. All values are nominal and to the best of our experience are true and accurate.
4. Non cogged V-belts may be pretensioned an additional 0.5%.
5. NK = Non-Cogged.