


YPF

Y-Top Solid Profile

Material:	Volta PF, Beige
Hardness:	88 A / 37 D
Temp. Range:	-30° C to +60° C
Certifications:	FDA/EU

Coefficient of friction :	
Steel:	0.38
Aluminum:	0.38



YPF

BELT TYPE	DIMENSIONS W x H mm X mm	WEIGHT kg/m	MIN. PULLEY Ø mm	MAX. WORK LOAD kg	PULL FORCE (kg) AT PRETENSION		
					1 %	2 %	3 %
YPF-13/A	13 x 15	0.15	143	33	5.3	10.6	15.9
YPF-17/B	17 x 18.5	0.24	175	52	8.3	16.7	25
YPF-22/C	22 x 24.5	0.42	235	87	13.9	27.8	41.7

Notes:


1. Pull Force in tables relate to Steel and Aluminum pulleys. Multiply given values by 0.9 for Cast Iron and 0.8 for wet pulleys.
2. All values are nominal and to the best of our experience are true and accurate.

YPF

Y-Top Solid Profile

Material:	Volta PF, Beige
Hardness:	88 A / 37 D
Temp. Range:	-20° F to +140° F
Certifications:	FDA/EU

Coefficient of friction :	
Steel:	0.38
Aluminum:	0.38



YPF

BELT TYPE	DIMENSIONS W x H inch X inch	WEIGHT lbs/ft	MIN. PULLEY Ø inch	MAX. WORK LOAD kg	PULL FORCE (lbs) AT PRETENSION		
					1 %	2 %	3 %
YPF-13/A	1/2 x 19/32	0.10	5 5/8	72	11.5	23	34.5
YPF-17/B	5/8 x 47/64	0.16	7	115	18.3	36.6	55
YPF-22/C	7/8 x 31/32	0.28	9 1/8	192	30.6	61.2	92

Notes:

1. Pull Force in tables relate to Steel and Aluminum pulleys. Multiply given values by 0.9 for Cast Iron and 0.8 for wet pulleys.
2. All values are nominal and to the best of our experience are true and accurate.